

Neon. Pure Gas.

Description

Neon is a rare atmospheric gas which is odorless, colorless, tasteless, nontoxic, monatomic and chemically inert. The concentration of Neon in the atmosphere, by volume percent, is 1.8×10^{-3} . Neon is principally shipped and used in gaseous form for excimer lasers, plasma displays, light bulbs, neon signs and R & D laboratory research. Linde Gases Material Safety Data Sheets (MSDS) are available for Neon gas and should be used as guidelines in regard to first aid, methods of storage, handling and general use of Neon..

Purity specifications (Maximum impurity levels)*

Contaminant	Research Grade 99.999%	UHP Grade 99.996%
Carbon Dioxide (CO ₂)	0.5 ppm	1.0 ppm
Carbon Monoxide (CO)	0.5 ppm	1.0 ppm
Helium (He)	8.0 ppm	35.0 ppm
Methane (CH ₄)	0.5 ppm	1.0 ppm
Nitrogen (N ₂)	1.0 ppm	4.0 ppm
Oxygen (O ₂)	0.5 ppm	1.0 ppm
Water (H ₂ O)	0.5 ppm	1.0 ppm

*Higher purities are available upon request.

Cylinder information

Purity	Cylinder Size*	Valve Outlet*	Volume Liters	Gross Weight Lbs/Kg	Pressure Psig/Bar
Research Grade	300	580	7500	152/69	2400/167
	200	580	5000	125/57	1760/122
	80	580	2000	52/24	1925/134
	30	580	1000	25/11	2000/139
	LB	580/170	50	6/3	2000/139
UHP Grade	300	580	7500	152/69	2400/167
	200	580	5000	125/57	1760/122
	80	580	2000	52/24	1925/134
	30	580	1000	25/11	2000/139
	LB	580/170	50	6/3	2000/139
Non-Refillable Cylinders	320	580	400	13/6	1625/113
	330	580	200	9/4	1250/87
	330	580	100	9/4	600/42
	340	580	50	6/3	725/51
	340	580	25	6/3	350/25

*Additional cylinder sizes and/or valve outlets are available upon request.

Physical constants

Chemical name	Ne	
Molecular weight	20.183	
Density of the gas at 70°F (21,1°C), 1 atm	0.05215 lb/ft3, 0.83536 kg/m3	
Specific gravity of the gas at 70°F (21,1°C), 1 atm	0.696	
Specific volume of the gas at 70°F (21,1°C), 1 atm	19.18 ft3/lb, 1.197 m3/kg	
Boiling point at 1 atm	-410.9°F, -246.0°C	
Melting point at 1 atm	-415.6°F, -248.7°C	
Critical temperature at 1 atm	-379.8°F, -228.8°C	
Critical pressure	384.9 psia, 26.54 bar	
Critical density	30.15 lb/ft3, 483 kg/m3	
Triple point at 6.29 psia (0.434 bar)	-415.4°F, -248.6°C	
Latent heat of vaporization at normal boiling point	37.08 Btu/lb, 86.3 kJ/kg	
Latent heat of fusion at triple point	7.14 Btu/lb, 16.6 kJ/kg	
Specific heat of the gas at 70°F (21,1°C), 1 atm	Cp	0.25 Btu/(lb) (°F) 1.05 kJ/(kg) (°C)
	Cv	0.152 Btu/(lb) (°F) 0.636 kJ/(kg) (°C)

Shipping data

Synonyms	He
CAS Register Number	7440-59-7
DOT Classification	Nonflammable gas
DOT Label	Nonflammable gas
Transport Canada Classification	2.2
Substance Identification (SI)	1046
UN Number	UN 1046
Hazards	High Pressure and suffocation
Toxicity (TL V)	Asphyxiant
Flammability Range (in air)	Nonflammable gas
Odor	None

Linde Electronics and Specialty Gases

One Greenwich Street, Suite 100, Stewartville, NJ 08886

Phone +1.908.329-9700 or +1.800.932-0624, Fax +1.908.329-9740, www.lindeus.com